



## PRODUCT DATA

### **Castrol EDGE with Titanium Fluid Strength Technology – The Advanced Full Synthetic from the Technology Leader in Motor Oil**

Castrol EDGE with Titanium Fluid Strength Technology is Castrol's most advanced oil.

#### **Features and Benefits:**

- Power = Strongest Dispersants– to fight power robbing deposits.
- Performance = Strongest oxidation control – to provide longest wear protection
- Protection = Lowest volatility - maximum performance during the entire drain interval

#### **Warranty and Protection Requirements:**

- Exceeds engine manufacturer's warranty requirements for applications requiring ILSAC GF-5, GF-4 and GF-3 and/or API SN, SM and SL

## Industry Specifications and OEM Approvals by Grade:

Specifications:	Edge with FST			
	0W-20	5W-20	5W-30	10W-30
API SN	X	X	X	X
SM	X	X	X	X
SL		X	X	X
SJ		X	X	X
ILSAC GF-5	X	X	X	X
ILSAC GF-4	X	X	X	X
ILSAC GF-3			X	X
ACEA A1	X	X	X	X
ACEA A5			X	X
ACEA B1	X	X	X	X
ACEA B5			X	X
Ford WSS-M2C153-H		X		
Ford WSS-M2C929-A			X	
Ford WSS-M2C930-A		X		
Ford WSS-M2C945-A		X		
Ford WSS-M2C946-A			X	
GM 4718M*			1(see below)	
GM 6094M*			1(see below)	X
dexos 1 performance requirements*		X	X	

1. GM 4718M and GM 6094M are obsolete. Superseded by dexos 1

\*use recommended viscosity grade, SAE 5W-30

## Typical Properties:\*

	0W-20	5W-20	5W-30	10W30
Viscosity @ 100° C, cst	8.6	9.1	9.8	11.4
Viscosity @ 210° C, cst	54.4	56.1	OK	64.2
Viscosity @ 40° F, SUS	45	49.9	OK	OK
Viscosity Index	161	161	166	OK
Low Temperature (°C)				
Cranking Viscosity, cP max	OK	OK	OK	OK
Low Temperature (°C)				40000@
Pumping Viscosity, cP max	OK	OK	OK	-30
HT/HS Viscosity, cP min	OK	OK	OK	OK
Pour Point, °F (°C) max	-38(-39)	-38(-39)	-27(-33)	-33(-36)
Flash Point, PMCC, °C min	OK	OK	OK	OK
Density @ 15 °C Relative	0.865	OK	0.865	0.865
Pounds Per Gallon	7.129	7.807	7.129	7.129

\* Due to continual product research and development, the information contained herein is based on products purchased in the U.S. subject to change without notification. Typical properties may vary slightly.

## Part Numbers and UPCs

### Packaged Goods

SAE Grade	0W-20	5W-20	5W-30	10W-30
Case Size	6/1 Qt	6/1 Qt	6/1 Qt	6/1 Qt
Case Part No.	6240	6242	6243	6241
Bottle/Unit UPC	0-7919126240-5	0-79191-26242-	0-79191-26243-	0-79191-26241-
Case UPC	0-79191-06240-1	0-79191-	0-79191-	0-79191-

### Bulk/Drum

SAE Grade	0W-20	5W-20	5W-30
Unit Size	55 Gal Drum	55 Gal Drum	55 Gal Drum
Part No.	55240	55241	55242

### Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the applications referred to above and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contact office, or via the Internet at [www.castrol.com/us](http://www.castrol.com/us). This product should not be used for purposes other than the applications referred to above. If disposing of used product, take care to protect the environment, return used oil to collection center.

BP Lubricants USA Inc.  
1500 Valley Road  
Wayne, NJ 07470  
Telephone: 1.800.462.0835  
[contactus@bp.com](mailto:contactus@bp.com)  
©2010 BP Lubricants USA Inc. All rights reserved.

[www.castrol.com/us](http://www.castrol.com/us)